



第23吉野号 (200t吊搭載)

定格総荷重表 200t吊クローラークレーン(KH1000L) 特殊								単位:t
フーム長さm 作業半径m	33.0m	36.0m	39.0m	42.0m	45.0m	48.0m	51.0m	54.0m
9.0	112.2							
10.0	94.6	94.4	92.8					
12.0	71.8	71.5	71.3	71.1	71.0	69.9		
14.0	57.4	57.1	57.0	56.7	56.6	56.5	56.2	56.0
16.0	47.5	47.2	47.1	46.8	46.7	46.6	46.3	46.0
18.0	40.4	40.1	39.9	39.7	39.5	39.4	39.1	38.8
20.0	35.0	34.6	34.4	34.2	34.0	33.9	33.6	33.3
22.0	30.7	30.4	30.2	29.9	29.7	29.6	29.3	29.0
24.0	27.3	26.9	26.7	26.5	26.3	26.2	25.8	25.5
26.0	24.5	24.1	23.9	23.6	23.5	23.3	23.0	22.7
28.0	22.2	21.8	21.6	21.3	21.1	20.9	20.6	20.3
30.0	20.3	19.8	19.6	19.3	19.1	18.9	18.6	18.3
32.0		18.2	17.9	17.6	17.4	17.2	16.8	16.6
36.0				14.8	14.6	14.4	14.0	13.7
40.0					12.5	12.2	11.9	11.6
44.0							10.2	9.8
48.0								8.5
フックブロック質量 (ton)								
フックの種類	200t用	100t用	60t用	25t用	12.5t用			
質量	2.6	1.4	1.2	0.85	0.5			

第23吉野号	尺度 1:500
KH-1000L 定格総荷重表	H24.07.01
吉野建設株式会社	