



第35吉野号

(100t吊クローラークレーン搭載)

定格総荷重表 100t吊クローラークレーン(KH500-3)											単位:t
ブーム長さm 作業半径m	31.0m	37.0m	43.0m	49.0m	55.0m	58.0m	61.0m	64.0m	67.0m	70.0m	73.0m
8.0	55.6										
9.0	50.2	50.1									
10.0	43.0	42.7	36.7								
12.0	33.2	32.9	32.6	28.5	24.5	21.9					
14.0	26.8	26.5	26.2	26.0	22.9	20.7	18.7	18.5	17.0	15.5	
18.0	19.1	18.8	18.5	18.2	17.9	17.8	16.8	16.1	15.6	14.0	12.6
20.0	16.6	16.3	16.0	15.7	15.4	15.2	15.0	14.9	14.7	13.3	12.0
22.0	14.6	14.3	14.0	13.7	13.4	13.2	13.0	12.9	12.7	12.5	11.3
24.0	13.0	12.7	12.3	12.1	11.7	11.6	11.4	11.2	11.1	10.9	10.6
26.0	11.7	11.3	11.0	10.7	10.4	10.2	10.0	9.9	9.7	9.5	9.3
28.0	10.5	10.2	9.9	9.6	9.2	9.1	8.9	8.7	8.6	8.4	8.2
30.0		9.2	8.9	8.6	8.3	8.1	7.9	7.8	7.6	7.4	7.2
32.0		8.4	8.1	7.8	7.4	7.3	7.1	6.9	6.8	6.6	6.4
36.0			6.7	6.4	6.1	5.9	5.7	5.6	5.4	5.2	5.0
40.0				5.4	5.0	4.9	4.7	4.5	4.3	4.0	3.7
44.0				4.5	4.2	3.9	3.7	3.5	3.3	3.0	2.7
48.0					3.4	3.1	2.9	2.6	2.4	2.2	1.9
52.0							2.2	2.0	1.8	1.5	
54.0							1.9	1.7	1.5		
フックブロック質量 (ton)											
フックの種類	100t用	60t用	25t用	12.5t用	10.0t用						
質量	1.4	0.95	0.73	0.5	0.37						

第35吉野号	尺度 1:500
KH500 定格総荷重表	H24.07.01
吉野建設株式会社	